

MONOLITE® FOG COAT BONDING CEMENT COATING



Revive the existing color and natural beauty of stucco with MONOLITE® Fog Coat. Or, use MONOLITE Fog Coat to eliminate color differences caused by job site conditions like changes in the weather.

Fog Coat is a spray-applied Portland cement coating which cures to become an integral part of the stucco surface to which it is applied. It comes in all colors, with the color built into the product. It will not chip or peel like conventional paint.

Designed for a variety of stucco finishes:

- Cures to become an integral part of the stucco
- Available in all colors
- Won't chip or peel like conventional paint
- An economical way to revive aging stucco
- A fast way to "even-out" color variations

Fog Coat is manufactured to MONOLITE standards—the benchmarks for quality, consistency and reliability you can expect from all our products. We package Fog Coat in convenient, easy-to-handle 25 pound bags. A 25 pound bag makes 9 to 10 gallons of sprayable Fog Coat—enough to cover up to 1,000 square feet.

DESCRIPTION

Use: MONOLITE® Fog Coat provides a durable and long-lasting coating for existing stucco.

COMPOSITION

MONOLITE® Fog Coat is formulated with Portland cement, hydrated lime and mineral color pigments.

PACKAGING

Available in 25 lb. bags

STORAGE

Store under cool, dry conditions. Avoid direct contact with the ground. Properly stored MONOLITE® Fog Coat has a useable lifetime of approximately six (6) months from date of manufacture.

COVERAGE

Approximate coverage, when applied according to manufacturer's recommendations, is 800 to 1,000 sq. ft. per 25 lb. bag.

JOB PROCEDURE

A. CONDITION OF BASE: MONOLITE® Fog Coat should NOT be used over painted or sealed stucco surfaces. The stucco must be free of dirt and foreign material. Contact your MONOLITE representative for application over smooth or unusual surfaces.

B. Mixing

- 1) Place 3 gallons of potable water in a clean, empty 5-gallon pail.

- 2) Add contents of 25 lb. bag of MONOLITE® Fog and mix to an even, lump-free paste.
- 3) Allow to stand for 20 minutes.
- 4) Mix while adding sufficient water to achieve a milky consistency.
- 5) Separate material equally into two 5-gallon pails. Add more water and mix to sprayable consistency. Do NOT use more than a total of 10 gallons of water for each 25 lb. bag of Fog Coat.
- 6) Immediately strain into the sprayer tank using a painter's strainer or nylon stocking.
- 7) Apply as recommended, agitating frequently during application to avoid separation.

C. APPROXIMATE FOG COAT COVERAGE: A 25 lb. bag makes 9 to 10 gallons of sprayable Fog Coat covering 800 to 1,000 sq. ft.

D. FOG COAT APPLICATION AND TIPS: Spray-apply using a hand pump, compressed air tank sprayer or modified painter's airless sprayer.

- Wall surface must be cool and clean.
- During dry and hot weather conditions apply a light water mist to the wall 30 minutes before applying Fog Coat. Hot, dry walls may dry light and chalky.
- Apply using a circular motion holding the nozzle 12 to 18 inches from the wall. Avoid overloading an area. Work up and down, and side-to-side being sure to catch all angles of the texture.
- Always apply Fog Coat end-to-end and top to bottom or to a prominent architectural break.
- For complete and better coverage, two application coats are recommended.

NOTE: Immediately after drying, the Fog Coat overspray should be brushed off aluminum and painted trim to prevent etching.

CURING

Lightly dampen with water 24 hours after application of MONOLITE® Fog Coat to assist curing. This is essential during hot weather. Complete curing requires several days, and normal chalkiness will decrease as curing takes place.

MATERIAL STANDARDS

White Portland Cement: Type 1 ASTM C-150
Federal Spec SS-C1950/3

CAUTIONS, LIMITATIONS AND PROPERTIES

Colors may vary due to weather and other job conditions. Before applying MONOLITE® Fog Coat, a sample should be applied and allowed to cure for color approval.

Monolite Stucco Products

Manufactured by Squires-Belt Material Co.
4567 Federal Blvd., San Diego, CA 92102
619-266-6100 • www.monolitestucco.com

