

MONOLITE® STUCCO

Monolite® Interior Stucco Specifications

Monolite® Interior Stucco is designed primarily for interior smooth trowel application over a gypsum plaster basecoat.



BASIC USES

Monolite® Interior Stucco is designed for interior use over all accepted plaster bases as described in ASTM C 842.

ADVANTAGES

- A. Uniformity – Excellent spread and working qualities.
- B. Strength - Hard, durable and fire resistant for interior applications.
- C. Composition - A mechanically blended compound of gypsum, hydrated lime, inert aggregates, and proprietary ingredients packed in sealed multi-wall bags. DOES NOT CONTAIN ASBESTOS.

INSTALLATION

A: HAND APPLICATION:

- 1) Prior to the application of interior stucco finish, the gypsum base coat shall be thoroughly dry.
- 2) Smooth finish plasters should be applied at a thickness of not more than 1/16". Texture finishes should be applied at a thickness of not more than 1/18". Spread on an even coat, then trowel to desired finish.

B: MIXING:

- 1) Power mixing with clean water only for at least 10 minutes is recommended.
- 2) Use within one hour after mixing.

C. CURING:

Under moderate weather conditions the stucco finish will cure itself and reach final hardness in 72 hours.

LIMITATIONS

- 1) Not for exterior use.
- 2) Not to be used in interior areas where directly exposed to free water or severe moisture conditions.

APPLICABLE STANDARDS

Monolite® Stucco conforms to the standards established by the Stucco Manufacturers Association.

Complies with: ASTM-C28

Hydrated Lime: ASTM C-206

Silica Sand: ASTM C-35

PACKAGING

Monolite Stucco is available in 90lb Sacks (40.9kg.)



Monolite Stucco Products

Manufactured by Squires-Belt Material Co.
4567 Federal Blvd., San Diego, CA 92102
619-266-6100 • www.monolitestucco.com