



Monolite® Stucco

Monolite® Interior Stucco Specifications

Description: Monolite® Interior Stucco is designed primarily for interior smooth trowel application over a gypsum plaster basecoat.

Basic Uses

Monolite® Interior Stucco is designed for interior use over all accepted plaster bases as described in ASTM C 842.

Advantages

- A. Uniformity – Excellent spread and working qualities.
- B. Strength - Hard, durable and fire resistant for interior applications.
- C. Composition - A mechanically blended compound of gypsum, hydrated lime, inert aggregates, and proprietary ingredients packed in sealed multi-wall bags. DOES NOT CONTAIN ASBESTOS.

Installation

A. Hand Application:

1. Prior to the application of interior stucco finish, the gypsum base coat shall be thoroughly dry.
2. Smooth finish plasters should be applied at a thickness of not more than 1/16" Texture finishes should be applied at a thickness of not more than 1/18" Spread on an even coat, then trowel to desired finish.

B. Mixing:

1. Power mixing with clean water only for at least 10 minutes is recommended.
2. Use within one hour after mixing.

C. Curing:

1. Under moderate weather conditions the stucco finish will cure itself and reach final hardness in 72 hours.

Limitations:

1. Not for exterior use.
2. Not to be used in interior areas where directly exposed to free water or severe moisture conditions.

Applicable Standards

Monolite® Stucco conforms to the standards established by the Stucco Manufacturers Association.

Complies with: ASTM-C28

Hydrated Lime: ASTM C-206

Silica Sand: ASTM C-35

Packaging:

Monolite Stucco is available in 90lb Sacks (40.9kg.)

Manufacturer

Squires-Belt Material Co.

San Diego CA, 92101

619.266.6100