

MONOLITE® VENETIAN INTERIOR PLASTER¹

Monolite Venetian Interior Plaster finish is a blend of proprietary ingredients, that when mixed and applied properly, achieves a unique marbled, smooth surface.



COLOR

Custom colors only, according to architects specifications.

INSTALLATION

HAND APPLICATION:

Venetian Plaster finish may only be applied by Squires-Belt approved contractors. Contact Squires-Belt for list of contractors.

MIXING

Proprietary to approved applicators methods.

RECOMMENDED BONDING AGENT

Plaster-Weld®, manufactured by Larson Products Corp.

CURING

Under moderate weather conditions the Venetian Plaster finish will cure itself and will reach final hardness in 72 hours.

PACKAGING

90 lb. Sack (40.9 kg)

APPLICABLE STANDARDS

Monolite Venetian Plaster Finish conforms to standards established by the Stucco Manufacturers Association.

Hydrated Lime: ASTM C-206

Silica Sand: ASTM C-35

Complies with ASTM C-28

LIMITATIONS:

Monolite Venetian Plaster Finish must not be used over STRUCTO-LITE Plaster or a basecoat with a lightweight aggregate. PVA based bonders must not be used as they can cause delamination of plaster finishes.

JOB REFERENCES:

Escondido Performing Arts Center, Escondido, CA.

Aviara Four Seasons Resort, Carlsbad, CA.

University of California San Diego, Beckman Research Institute, San Diego, CA.

¹June 26, 2006 \\:\PLASTER\CERT-Venetian.wpd.wpd



Monolite Stucco Products

Manufactured by Squires-Belt Material Co.
4567 Federal Blvd., San Diego, CA 92102
619-232-8188 • www.monolitestucco.com