

# MATERIAL SAFETY DATA SHEET

## DURALITE PREMIUM BOND



### PRODUCTS COVERED BY MSDS

**DURALITE PREMIUM BOND** Monolite Blended Products  
Duralite Mexico A Division of Squires-Belt Material Co.  
Duralite Smooth Finish PO Box 152047  
4567 Federal Blvd.  
San Diego, CA 92102  
Office (619) 266-6100 Fax (619) 266-6122  
www.monolitestucco.com

Date: December 19, 2005

### SECTION 1: PRODUCT IDENTIFICATION

Manufacturers' identification Sku: DPBOND  
Product Class: Exterior Foam Coating Plaster  
Trade Name: Duralite Premium Bond

### SECTION 2: INFO ON INGREDIENTS

COMPONENTS	CAS NO.	DOD	NIOSH	KNOWN TO BE PRESENT
Portland Cement	65997-15-1	6050.5-L	VV8770000	3 CAO.SIO*2/ (ing 2)
Silica Sand	12001-26-2	2.8g/cc	92-100.92	Silica Dust
Calcium Carbonate	1317-65-3	15<1%+2	N/A	1% Silica Dust
Methoxyethylcellulose	68441-63-4	1.28-1.30g	N/A	N/A

### SECTION 3: PHYSICAL DATA

Boiling Range: N.A.  
Vapor Pressure: mmHg at 20°C  
Vapor Density: 1.38–1.40 g/cm<sup>3</sup> (20 c)  
Evaporation Rate: N.A.  
Weight Per Gallon: N.A.  
%Volatile by Volume: N.A.  
%Volatile by Weight: N.A.

### SECTION 4: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification: N.A.  
Lowest Flashpoint: NOT DETERMINED  
Extinguishing Media: Water spray jet / Foam  
Fire and Explosion Hazards: N.A.  
Fire Fighting Procedures: Water spray jet / Foam

## SECTION 5: HEALTH HAZARD DATA

Effects of Overexposure:	Inhalation: Inhalation of dust can cause headache, nausea, and irritation of nose, throat or lungs. Eye Contact: Severe irritation. Skin Contact: Prolonged or repeated skin contact with wet material can cause a slight irritation.
Primary Routes of Entry:	Inhalation, Skin and Eye Contact
Emergency and First Aid Procedures:	Inhalation: Remove to fresh air. Eye Contact: Flush eyes with running water for at least 15 minutes. Consult a physician if irritation persists. Skin Contact: Wash affected area thoroughly with soap and water. Consult a physician if irritation persists. Ingestion: If swallowed, give at least two (2) glasses of water and consult a physician. Never give anything by mouth to an unconscious person.

## SECTION 6: REACTIVITY DATA

Stability:	Stable
Hazardous Polymerization:	None
Hazardous Decomposition Products:	None
Incompatibility (Materials to avoid):	

## SECTION 7: SPILL OR LEAK PROCEDURES

Personal Protection:	See section V Health Hazard Data
Procedures:	Use respiratory protection if dust becomes airborne.
Waste Disposal:	Dispose of in accordance with applicable Federal, State, and Local regulations. Keep spills and runoff out of municipal sewers and open bodies of water.

## SECTION 8: SAFE HANDLING AND USE INFORMATION

Respiratory Protection:	Non-required for normal use of this product. If material is sanded or ground when dry, approved respirators for dust should be provided and used. As with any safety product, workers using respirators should be trained in the proper selection, use and care.
Ventilation:	Local Ventilation.
Protective Gloves:	Rubber or neoprene gloves for protection against wet material
Eye Protection:	Use goggles. Full flow eyewash station.

## SECTION 9: SPECIAL PRECAUTIONS

Squires-Belt Material Co. as a blender of processed material in the state of California is required by Proposition 65 to warn that one or more of the components contained in this product could contain chemical known to the state of California to cause cancer, birth defects or other reproductive harm. The state of California requires this warning in the absence of definitive testing, to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacture, distribution and intended use. This information is furnished with out warranty, representation, inducement or license of any kind, except that it is accurate to the best of Squires-belt Material Co. knowledge or is obtained from sources believed to be accurate. Customers are encouraged to conduct their own test. Before using any product, read labels and instructions.